

INTRODUCING DEP600

**LARGE
COLOR
DISPLAY**

**EASY
ICON
NAVIGATION**

**USB
BACKUP
RESTORE**

**WTC
WELD
CONTROL
INTERFACE**

Easy to use.
Provides
real-time
diagnostics
and
configuration
capability.



**CLEAR
DISPLAY
FOR
ALERTS**

**QUICK
ACCESS
TO WELD
DATA**

Improved plant
efficiency with
real-time
diagnostic
information

Connectivity options
with multiple weld
controls across plant
via EtherNet or a
single control via
Serial/EtherNet

#0	DC V	Sec I	Pri I	HFC	0	LV	0
MAX	0	0	0	OnTime	0	CFACT	0
AVG	0	0	0	%I	0	SCH	0
MIN	0	0	0	CONT	0	Target	0

STEPPER APPROACHING MAX:

HFC 0
OnTime 0
%I 0
CONT 0

**CHECK
WELD
STATUS**

Easy back-up and
restore capability
for weld control
maintenance and
deployment

Saves time by
configuring once
and applying
many times



DEP600

PRODUCT SPECIFICATIONS:

WTC Part Number	937-0060
Display	7 inch (178mm) Full Color
Back light	LED
Operator Input	Touch Screen and Keypad
Dimensions (W x H x T)	8.1" (207mm) x 10.4" (265mm) x 1.2" (28mm)
Weight	2.6 lb (1.18kg)
Connectivity	EtherNet/Serial: DB15 to DB15, Y-Cable - DB15 to RJ45 and 9 pin connector
USB Host	1 x USB 2.0 Type A
Operating Temperature	0° - 45° C

OPTIONAL ACCESSORIES:



DEP Hanger Bracket Kit
830-1250



DB15 to SDL Adapter Cable for
legacy products
205-3607